

Wood fly ash, sawdust and limestone powder wastes, used as replacements in concrete

*Bianca Suciu**

* Student of third year, **Faculty of Mechatronics and Integrated Armament Systems, Military Technical Academy**, Bucharest.

* Author to whom correspondence should be addressed;
e-mail: bianca.suciu7@gmail.com

Academic year: 2015-2016

The research was made in the laboratories of The School of Engineering in Bilbao.

with the presence of limestone powder and wood ash waste, according to other tests made only on sawdust concrete or wood ash concrete or limestone concrete.

- All the specimens show good performance in drying shrinkage results due to the fact that the wood fibers maintain the water in cells in time.

Acknowledgments

The author appreciates the support received from the Basque Regional Government through IT781-13 and also is thankful to the Precast Company Alberdi S.A. and the company Smurfit Kappa Nervión, for providing the materials used throughout the work.

The investigation was made with the support of PhD student Maggi Isabel Madrid Guerrero and Associate Professor Jesús Cuadrado Rojo.

References

- [1] Sakai K, Noguchi T. The sustainable use of concrete. CRC Press – Taylor & Francis Group; 2012. ISBN 978-0415667203.
- [2] Mahasenan, Natesan; Steve Smith; Kenneth Humphreys; Y. Kaya (2003). "The Cement Industry and Global Climate Change: Current and Potential Future Cement Industry CO₂Emissions". Greenhouse Gas Control Technologies – 6th International Conference. Oxford: Pergamon. pp. 995–1000. ISBN 978-0-08-044276-1.
- [3] Saeid Hesami, Amir Modarres, Mostafa Soltaninejad, Hesam Madani. Mechanical properties of roller compacted concrete pavement containing coal waste and limestone powder as partial replacements of cement. Construction and Building Materials 111 (2016) 625–636
- [4] http://www.researchgate.net/post/What_is_green_concrete.
- [5] Bonavetti V, Donza H, Menéndez G, Cabrera O, Irassar EF. Limestone filler cement in low W/C concrete: a rational use of energy. Cem Concr Res 2003;33(6):865–71.
- [6] Poppe AM, De Schutter G. Cement hydration in the presence of high filler contents. Cem Concr Res 2005;35(12):2290–9.
- [7] Edward. Bwayo, S. K. Obwoya THERMAL CONDUCTIVITY OF INSULATION BRICK DEVELOPED FROM SAWDUST AND SELECTED UGANDA CLAYS IJRET: International Journal of Research in Engineering and Technology eISSN: 2319-1163 | pISSN: 2321-7308
- [8] I.M. Nikbin, M.H. a Beygi, M.T. Kazemi, J. Vaseghi Amiri, S. Rabbanifar, E.Rahmani, et al., A comprehensive investigation into the effect of water to cement ratio and powder content on